Planar Contour Primitive Recognition of Thin Sheet Part Dimensional Inspection System

J. G. Wu^{1, a}, K. F. He^{2, b}, B. Qin^{3, c}

^{1,3}Hunan Provincial Key Laboratory of Health Maintenance for Mechanical Equipment, Hunan University of Science and Technology, Xiangtan, 411201, China

²Engineering Research Center of Advanced Mine Equipment, Ministry of Education, Hunan University of Science and Technology, Xiangtan, 411201, China

^ajgwuhust@gmail.com, ^bhkf791113@163.com, ^cqinbin505@sina.com.

Keywords: curvature, HOUGH transform, planar contour, primitive recognition

Abstract. According to the two indices of inspection accuracy and inspection speed, a planar contour primitive recognition method of thin sheet part dimensional inspection system based on curvature and HOUGH transform is proposed. A contour point classification algorithm based on neighborhood values is developed, and a curvature threshold method is selected to filter the contour points, and a projection height method is selected to distinguish the property of the primitive and classify the contour points, and the straight line primitive and arc primitive segmentation and merging algorithms are constructed respectively by HOUGH transform. The inspection accuracy and inspection speed of the proposed method are compared and analyzed by contrast experiments between the proposed method and four dominant point detection methods such as Chung & Tsai method and so on. The dominant point detection ability of the proposed method is tested by a simulation planar contour which includes all kinds of dominant points. The experimental results indicate that the proposed method can recognize primitives exactly, the inspection speed is fast and the universality is good.

Introduction

The thin sheet part dimensional inspection system based on machine vision is a high-accuracy, on-line real time inspection system. The pixel set which is single-pixel width and connected is obtained after the edge detection of the inspected part image, and the primitives such as line, arc and circle are made up of the single-pixel width and connected pixels which belong to the same primitives, and the planar contour is made up of those primitives. The planar contour primitive recognition is the key and essential step of the thin sheet part dimensional inspection system, the recognition precision will affect the veracity of the subsequent dimension inspection directly, and the recognition efficiency will affect the real-time of the inspection system directly. The intersection point between primitives is called dominant point, so the dominant point detection of the planar contour is the key of the planar contour primitive recognition. The dominant point detection of the planar contour is investigated widely and deeply by many domestic and overseas scholars, and much dominant point detection methods are proposed. The existing dominant point detection methods can be classified into three categories, dominant point detection method based on gray character of image, dominant point detection method based on mathematical morphology, dominant point detection method based on edge information of image. The existing dominant point detection

methods have the disadvantages such as large calculated amount, low inspection accuracy, bad compatibility, and so on, and it is hard to be used in high precision and real-time situation. A planar contour primitive recognition method of thin sheet part dimensional inspection system based on curvature and HOUGH transform is proposed based on intensive study of existing dominant detection methods.

Planar contour primitive recognition based on curvature and HOUGH transform

The procedures are as follows. (1) The contour points are classified according the neighborhood values, the contour points which may be corner are picked out, and these contour points are called candidate contour points. (2) The discrete curvature values of all candidate contour points are calculated with 11 point k-curvature method, the discrete curvature threshold value is calculated according to the discrete curvature values of all candidate contour points, the candidate contour points which discrete curvature value is greater than threshold value are picked out, and these candidate contour points are called first filter candidate contour points. (3) The first filter candidate contour points are classified with projection height method. (4) The false dominant points of the arc primitives are rejected and the inflection points of the arc primitives are added with arc primitive segmentation and merging algorithms based on HOUGH transform, the candidate contour points after this step processing are called secondary filter candidate contour points. (5) The secondary filter candidate contour points are classified with projection height method. (6) The false dominant points of the line primitives are rejected and the tangent points of the line primitives are added with line primitive segmentation and merging algorithms based on HOUGH transform, so far all false dominant points are rejected and the inflection points and the tangent points are added, the candidate contour points after this step processing are dominant points. (7) The dominant points are classified and the property of the primitives on either hand of dominant point is distinguished with projection height method. (8) The dominant points are saved in sequence.

Classification of contour point based on neighborhood value. As shown in figure 1 (a), the pixel P has two horizontal neighboring pixels and two vertical neighboring pixels (identified with t), and has four diagonal neighboring pixels (identified with s), all the neighboring pixels and diagonal neighboring pixels are called as eight neighbourhood of the pixel P. In order to distinguish them, each pixels of eight neighbourhood are marked, as shown in figure 1 (b). It is specified that the eight neighbourhood value of the 0 neighbourhood pixel is 0, the eight neighbourhood value of the 1 neighbourhood pixel is 1, and the rest may be deduced by analogy.

Fig. 1 Eight neighborhood of pixel P

The planar contour which obtained after edge detection is saved independently and consecutively at the order of the connected sequence. It is supposed that there is a contour point C_i , the contour point before it is C_{i-1} , the contour point after it is C_{i+1} , the eight neighborhood value of C_{i+1} in eight neighborhood of C_i is abbreviated as eight neighborhood value of C_i , the eight neighborhood value of C_i in eight neighborhood of C_{i-1} is abbreviated as eight neighborhood value of C_{i-1} . If eight neighborhood value of C_i is unequal to that of C_{i-1} , then C_i may be a corner, if eight neighborhood value of C_i is equal to that of C_{i-1} , then C_i cannot be a corner. So

the contour points can be classified according the eight neighborhood value, the contour point that cannot be corner is marked, the curvature of the marked contour point will not be calculated at later curvature calculation of contour points, thus calculation amount is reduced and real-time of the system is improved.

Filter of candidate contour point by curvature threshold method. The discrete curvature values of all candidate contour points are calculated with 11 point k-curvature method. It is supposed that the contour C has N contour points $P_i = (x_i, y_i) (i = 0, 1, \dots, N-1)$, the calculation formula of discrete curvature k_i is as follows.

$$k_i = \text{sign}((x_i - x_{i-5})(y_{i+5} - y_i) - (y_i - y_{i-5})(x_{i+5} - x_i)) \frac{\mathbf{R}_{i1} \mathbf{R}_{i2}}{\|\mathbf{R}_{i1}\| \|\mathbf{R}_{i2}\|} \quad (1)$$

where, $\mathbf{R}_{i1} = \mathbf{P}_i - \mathbf{P}_{i-5}$, $\mathbf{R}_{i2} = \mathbf{P}_{i+5} - \mathbf{P}_i$, $\mathbf{P}_i = [x_i, y_i]^T$.

After the curvatures of candidate contour points are calculated, the candidate contour points are filter with curvature threshold, the candidate contour points which cannot be corner are rejected. The selection of the curvature threshold is the key of the dominant point detection method based on curvature, oversize curvature threshold will miss some valid contour points, and undersized curvature threshold will generate false dominant points. The proposed method has the segmentation and merging of straight line primitive and arc primitive in subsequent, the missed valid contour points will be added and false dominant points will be rejected, so the selection of the curvature threshold value is not key. After several experiments of many contours, it is indicated that when the curvature threshold is set as the average of the curvatures of all candidate contour points in the contour, neither the corners are missed nor much false dominant points are added. So the curvature threshold of the contour is set as the average of the curvatures of all candidate contour points in the contour automatically, therefore the curvature threshold does not need to be set by man-machine interaction method manually, thereby the intelligence and compatibility of the inspection system is improved.

Discrimination of primitive property and classification of contour points by projection height method. If the primitive is wanted to be recognized, the property of the primitive between two dominant points must be known. The property of the primitive between two dominant points is discriminated and dominant points are classified with projection height method based on projection height form dot to straight line. As shown in figure 2, P_{i-1} , P_i , P_{i+1} are supposed as three adjacent candidate contour points, C is supposed as a part of a closed contour. P_i is supposed as the current candidate contour point, a straight line $P_i P_{i-1}$ is draw from P_i to P_{i-1} , the projection height H_j of all contour points CP_j between P_i and P_{i-1} to straight line $P_i P_{i-1}$ are calculated. The threshold T is set as 0.5, two accumulators are defined, one is the line accumulator LineAccu the other is the arc accumulator ArcAccu, if $H_j > T$, then $\text{ArcAccu} = \text{ArcAccu} + 1$, otherwise $H_j \leq T$, then $\text{LineAccu} = \text{LineAccu} + 1$. After all contour points CP_j between P_i and P_{i-1} are calculated, if $\text{ArcAccu} > \text{LineAccu}$, then the primitive between P_i and P_{i-1} is arc, otherwise $\text{ArcAccu} \leq \text{LineAccu}$, then the primitive between P_i and P_{i-1} is straight line. In the similar way, the primitive between P_i and P_{i+1} can be discriminated. The type of P_i can be discriminated and classified according to the property of the primitive between P_i and P_{i-1} and the property of the primitive between P_i and P_{i+1} . The type of candidate contour point and dominant point is defined as follows according to the combination of straight line and arc. Type 1, straight line to straight line, type 2 arc to straight line, type 3 straight line to arc, type 4 arc to arc. After all candidate contour points of each contour are calculated, then all candidate contour points can be classified.

Fig. 2. Principle of projection height method

Segmentation and merging of arc based on HOUGH transform. As shown in figure 3 (a), it is supposed that contour $Q_j Q_{j+1}$ is formed by a convex arc and a concave arc which connected fair, after the candidate contour points are filtered by curvature threshold method, all candidate contour points are false dominant points, at the same time the inflection point between two arc is missed, after all the candidate contour points are classified by projection height method, the type of $P_1, P_2, \dots, P_{N-1}, P_N$ are type 4, the type of Q_j, Q_{j+1} is type 3 and type 2 respectively.

It is supposed that Q_j is the present processing candidate contour point which is abbreviated to the current point, the candidate contour point P_1 next Q_j is abbreviated to the next candidate contour point, the candidate contour point P_2 which is after Q_j two candidate contour point is abbreviated to the next to next candidate contour point. All contour points (including two candidate contour points) from current point Q_j to next candidate contour point P_1 are fitted with least square arc, the centre (a_1, b_1) and radius r_1 of arc are $Q_j P_1$ calculated and obtained. According to the principle of HOUGH transform arc detection, if next to next candidate contour point P_2 belongs to circle which contain the arc $Q_j P_1$, then the three-dimensional erect taper surface corresponding with next to next candidate contour point P_2 and that corresponding with arc $Q_j P_1$ are intersected at point (a_1, b_1, r_1) in the parameter space. Therefore the parameter space coordinates (a_1, b_1, r_2) of next to next candidate contour point P_2 which calculated and obtained according to $r_2 = \sqrt{(x-a_1)^2 + (y-b_1)^2}$ is the same point in the parameter space with (a_1, b_1, r_1) in theory. So the absolute value of the difference between r_2 and r_1 namely $\varepsilon_1 = |r_2 - r_1|$ is calculated, and ε_1 is compared with threshold $T=0.001$. If $\varepsilon_1 \leq T$, it is indicated that arc $Q_j P_1$ and arc $P_1 P_2$ belong to the same arc, and should be merged, the candidate contour property of the next candidate contour point P_1 is clear, the next to next candidate contour point P_2 is set as next candidate contour point and the calculation is continued and recycled. If $\varepsilon_1 > T$, it is indicated that arc $Q_j P_1$ and arc $P_1 P_2$ do not belong to the same arc, namely a dominant point is missed between next candidate contour point P_1 and the next to next candidate contour point P_2 . The mid-value point P (if the mount of the contour point between P_1 and P_2 is a even number, there are two mid-value point, one of the two mid-value point is selected discretionarily) of next candidate contour point P_1 and the next to next candidate contour point P_2 is selected and set as candidate contour point, the parameter space coordinates (a_1, b_1, r_3) of candidate contour point P is calculated and obtained according to $r_3 = \sqrt{(x-a_1)^2 + (y-b_1)^2}$, the absolute value of the difference between r_1 and r_3 namely $\varepsilon_2 = |r_3 - r_1|$ is calculated, and ε_2 is compared with threshold $T=0.001$. If $\varepsilon_2 > T$, then P is set as new next to next candidate contour point, if $\varepsilon_2 \leq T$, then P is set as new next candidate contour point. Then the calculation and compare is continued and recycled, until the interval between new next candidate contour point and new next to next candidate contour point is less than 1, the candidate contour property of the next candidate contour point P_1 is clear, and the candidate contour property of new next candidate contour point is set. The segmentation and merging result of arc $Q_j Q_{j+1}$ is shown in figure 3 (b), it is shown in figure 3 (b) that all false dominant points in the arc $Q_j Q_{j+1}$ have rejected, and the inflection point Q^* has added. Since circle is a special arc, it is specified that one of the candidate contour points is reserved and its type is set as type 4 after the segmentation and merging of circle.

Fig. 3. Principle of arc segmentation and merging based on HOUGH transform

Segmentation and merging of straight line based on HOUGH transform. As shown in figure 4 (a), contour $Q_j Q_{j+1}$ is formed by a straight line and a concave arc which connected fair, after the candidate contour points are filtered by curvature threshold method, all candidate contour points are false dominant points, at the same time the tangent point between the straight line and the arc is missed, after all the candidate contour points are classified by projection height method, the type of P_1, P_2, P_3, P_4 are type 1, the type of P_N is type 3, the type of Q_j, Q_{j+1} is type 1 and type 2 respectively. The procedure of the segmentation and merging of straight line based on HOUGH transform is basically the same as that of the segmentation and merging of arc based on HOUGH transform, merely here the principle of the segmentation and merging of straight line is HOUGH transform straight line detection, therefore the algorithm of the segmentation and merging of straight line is unnecessary to go into details. The segmentation and merging result of straight line is shown in figure 4 (b), it is shown in figure 4 (b) that all false dominant points have rejected, and the tangent point between the straight line and the arc Q^* has added.

Fig. 4. Principle of line segmentation and merging based on HOUGH transform

Experiment result and analysis

Compare analysis of detection accuracy and speed. Standard test image of dominant point detection Airplane is shown in figure 5 (a), the dominant point of the planar contour of the Airplane image is detected with Chung & Tsai, Sarkar, Freeman & Davis, Rattarangsi & Chin and the proposed method respectively, the detection results is shown in figure 5 (b), (c), (d), (e), (f). The Airplane contour has 38 dominant points, the correct rate, misjudgment rate, omissive judgment rate and detection time of the above 5 dominant point detection method are compared and analyzed, the result is shown in table 1. It can be known from table 1 that the proposed method can detect the dominant points of the contour 100 percent, and the detection time is less than that of others.

Fig. 5. Dominant point detection results of Airplane planar contour

Table 1 Dominant point detection effects of Airplane planar contour

Method	Correct rate	Misjudgment rate	Omissive judgment rate	Detection time (s)
Chung & Tsai	76.3	0	23.7	0.19
Freeman & Davis	60.5	0	39.5	0.28
Sarkar	78.9	0	21.1	0.15
Rattarangsi & Chin	68.4	0	31.6	0.14
Proposed method	100	0	0	0.09

Dominant point detection of simulation planar contour. Since the dominant point type of the Airplane planar contour is corner, in order to test the detection ability to other type dominant points and dominant point detection accuracy of the proposed method, a simulation planar contour which includes all kinds of dominant point is made particularly, the image of the simulation planar contour is shown in figure 6 (a), dominant point detection result is shown in figure 6 (b). When the simulation planar contour is made, the position of each dominant point is known, the position of each dominant point obtained by dominant point detection is compared with the known position of each dominant point, and the detection experiment results indicate that the position of each dominant point can be detected exactly with the proposed method.

Conclusion

A planar contour primitive recognition method of thin sheet part dimensional inspection system based on curvature and HOUGH transform is proposed in this paper. The procedures and realization of the method are discussed in detail, the inspection accuracy and inspection speed of the proposed method are compared and analyzed by contrast experiments between the proposed method and four dominant point detection methods such as Chung & Tsai method and so on, the dominant point detection ability of the proposed method is tested by a simulation planar contour which includes all kinds of dominant points. The experimental results indicate that the proposed method can recognize primitives exactly, the inspection speed is fast and the universality is good.

Acknowledgement

Financial support from CEEUSRO Special Plan of Hunan Province (2010XK6066), Aid Program for Science and Technology Innovative Research Team in Higher Educational Institutions of Hunan Province, Project Supported by Scientific Research Fund of Hunan Provincial Education Department (09C405), Ph.D. Start Fund (E50925), are gratefully acknowledged.

References

- [1] A. Masood: Pattern Recognition Vol. 41(2008), p. 227-239.
- [2] M. Majed, S. Pepe: Pattern Recognition Vol. 37(2004), p. 2113–2130.
- [3] F. Y. Shih, C. F. Chuang: Pattern Recognition Letters Vol. -4(2005), p. 931-937.
- [4] J. H. Han, T. Poston: Pattern Recognition Letters Vol. 22(2001), p. 1133-1144.