Electrochemical degradation of pharmaceutical compounds as Tetracycline in aqueous solution with BDD electrode

Carmen Brinzila^{1,2, a}, Lurdes Ciríaco², Maria Jose Pacheco², Ana Lopes²,
Romeo Cristian Ciobanu¹

¹Faculty of Electrical Engineering, The "Gheorghe Asachi" Technical University of Iasi, Bd. Professor Dimitrie Mangeron, n°21-23, 700050, Iasi, Romania

²UMTP and Department of Chemistry, University of Beira Interior, 6200-001 Covilhã, Portugal

^aemail, carmenbrinzila@gmail.com (corresponding author)

Keywords: Antibiotics, Boron Doped Diamond, Electrochemical degradation.

Abstract. Antibiotics named tetracycline (TC) are the most popular group of pharmaceutical compounds used in therapeutic purpose in human and veterinary medicine and in aquaculture, due to their characteristics as broad spectrum antibiotic. The tetracyclines are a group of natural and semisynthetic products that are bacteriostatic agents with activity against a wide variety of organisms, but of limited use today because of acquired resistance. Even at low concentrations, tetracycline and its metabolites may have a negative influence on the environment. Tetracycline is weakly metabolized or absorbed into the body, some of the ingested antibiotic being eliminated through urine and feces directly into the environment as most of the primarily unchanged form or secondary compounds. Nowadays tetracycline residues can be detected in surface water that was discharged from municipal wastewater treatment plants and agricultural drained. In this study, the degradation of tetracycline and the influence of experimental parameters (initial pH, initial concentration, different flow velocity (mL/s), solution temperature (°C), current intensity (mA)) on electrochemical degradation with BDD electrode were evaluated. The following parameters were analyzed for the samples collected during the electrochemical assays in electrochemical cell with stirrer and BDD/stainless steel electrodes: Chemical oxygen demand (COD), total organic carbon, nitrogen (total Kjeldhal, organic and inorganic), HPLC and UV-Visible absorption spectrophotometry.

Introduction

Due to the global consumption of antibiotics (100000-200000 tons per year), in recent years, an increasing concern focuses on the presence of pharmaceuticals in the aquatic environment. Among a variety of pharmaceuticals, antibiotics are most frequently detected in the environment that are difficult to be removed through conventional biological treatment methods.

Pharmaceuticals named antibiotics are potent bioactive chemicals that can be grouped by either their chemical structure or mechanism of action, and can be divided into different subgroups such as β -lactams, quinolones, tetracyclines, macrolides, sulphonamides and others [1].

Tetracyclines (TC) are a group of natural and semisynthetic products characterized by four rings structure with a carboxylamide functional group and as side chains, several other ionizable functional groups which are responsible for their charge (Fig. 1).

TC are amphoteric molecules having those ionizable groups that give a molecule its pKa, giving rise to negative, cationic, or zwitterion charged species [2].

TC are used as bacteriostatic agents, inhibit the synthesis of bacterial proteins, with activity against a wide variety of organisms in human and veterinary medicine as well in aquaculture for preventing or treating microbial infections [1,3]. Due to their antimicrobial proprieties, oxytetracyclines are used in controlling bacterial diseases of tree fruits in USA. Because of some characteristics such as: active on and inside the plant, tolerate oxidation, UV irradiation, rainfall and high temperature, TC are preferred in fruit growing industry becoming the main factor of environment problems.

Tetracycline group of antibiotics is the second most widely used antimicrobial in both production and usage, worldwide, with applications in human therapy and in the livestock industry, like aquaculture and veterinary medicine [4]. TCs are weakly metabolized or absorbed into the human or animal body, some of the ingested antibiotic being eliminated through urine and feces directly into the environment as most of the primarily unchanged form or secondary compounds.

The extensively use of TC has lead to a negative influence on the environment, even at low concentrations, tetracycline and its metabolites (4-epi-tetracycline) are later released into aquatic environment usually after the physical/chemical and biological process in wastewater treatment plants [5].

Nowadays tetracycline residues can be detected in surface water that was discharged from municipal wastewater treatment plants and agricultural drained. The presence of residual pharmaceuticals in the environment and in aqueous system constitutes a serious problem to environment due to their resistance to biological degradation processes used today in conventional treatment plants, and even in low concentration may produce serious toxic and other effects to humans and living organism [6-8]. With a growth of population, intensive agriculture and industrialization, a very important role today is played by clean water recovery processes from wastewater for reuse by elimination of antibiotics from terrestrial and aqueous resources.

Fig. 1. Tetracycline chemical structure

Several studies on degradation of tetracycline, using different technologies were conducted: using activated sludge processes [9], TiO₂ nanopore arrays electrode [10], TiO₂ and ZnO aqueous suspensions were also used in the photocatalytic oxidation of tetracycline, under simulated solar light [11], photocatalysis of TC with C–N–S tridoped TiO₂ material [12], electron pulse radiolysis [14-17], using Pt plates as anode [14], with Ti/RuO₂ anode [15].

In this study, the electrochemical reactions followed pseudo-first order kinetics. The same type of kinetics was observed in the anodic oxidation of tetracycline at a Ti/RuO₂–IrO₂ anode [16], where the degradation rate increased with current density and decreased with the increasing in the initial antibiotic concentration. Study of the influence of hydroxyl radicals' scavenger showed that anodic oxidation of tetracycline with this anode occurs mainly by direct electron transfer [3].

However, in all previous studies that have used active anodes, no significant levels of mineralization were achieved. In the present study, it is proposed the degradation of tetracycline using a boron-doped diamond (BDD) electrode, a non-active anode.

Recently BDD anodes have received growing attention due to chemical and electrochemical stability, good conductivity and due to his capacity to achieve increased rates of mineralization with very high current efficiencies. In fact, BDD has a long service-life, even when drastic oxidizing conditions are used. This material has a high O₂-overpotential and produces a high concentration of hydroxyl radical (·OH) on its surface during electrochemical process from water oxidation. (·OH) generated on BDD surface is non-selective, very powerful oxidizing agent, able to react with organics giving dehydrogenated or hydroxylated derivatives till is reached their complete mineralization (total conversion to CO₂, water and inorganic anions). Hydroxyl radicals formed from water discharged on the electrode's surface are the main species responsible for the oxidation of the pollutants.

Due to its upstanding proprieties (a large working potential window of more than 4 volts, particularly useful for water treatment applications; a high chemical stability even in strong acidic or alkaline medium; a non-poisoning of the surface thanks to the possibility of polarity reversal) BDD electrode has multiple applications with great result especially in destruction of organics for wastewater treatment from industrial effluents, organic matter oxidation, COD removal, inorganic matter oxidation [18-20].

Model TC solutions are used and different experimental conditions, namely, initial concentration, initial pH, applied current density, type and concentration of the electrolyte are also tested.

To study the influence of the experimental conditions on the degradation of the antibiotic, assays were performed at experimental conditions that allow kinetic and/or diffusive control, in order to determine medium mass transfer coefficients that help to predict degradation rates at experimental conditions other than those tested.

The evolution of the electrochemical degradation assays with time was followed by UV/Vis spectroscopy, by means of measurements of chemical oxygen demand, total organic carbon and by HPLC. Moreover, for some selected samples the identification and characterization of the analytes, namely degradation products, was achieved by HPLC.

In order to study the influence of the experimental conditions on the mineralization degree of the antibiotic pollutant, the ratio COD/TOC will be determined for the different experimental conditions tested and combustion efficiencies will be calculated.

The influence of the initial concentration and the hydrodynamics inside the electrochemical cell on the rate of electrodegradation and mineralization of TC using a BDD anode will also be assessed.

Experimental

Tetracycline used in this study was the alkali form, with the chemical formula $C_{22}H_{24}N_2O_8 \cdot xH_2O$, purchased from Sigma Aldrich (purity 99%) and used without further purification. All reagents were analytical grade from Fluka, Panreac or Sigma-Aldrich.

The cyclic voltammetric measurements were performed in a potentiostat/galvanostat VoltaLab PGZ 301. All electrochemical system was described elsewhere [3]. Tetracycline degradation experiments were conducted in batch mode, with recirculation, in an up-flow electrochemical cell, composed by a BDD anode (Diachem[®]) and a stainless steel cathode.

Degradation tests were monitored by the following determinations: total organic carbon (TOC) and total nitrogen (TN), measured in a Shimadzu TOC-V CPH analyser combined with a TNM-1 unit; chemical oxygen demand (COD), performed using closed reflux and titrimetric method; total Kjeldahl (TKN) and ammonia nitrogen ($N-NH_3$), determined according to standard procedures, using a Kjeldatherm block-digestion-system and a Vapodest 20s distillation system, both from Gerhardt. UV-Visible absorption spectra were also made, using a Shimadzu UV-1800 spectrophotometer. High performance liquid chromatography (HPLC) was performed using a Merck-Hitachi LaChrom Elite HPLC system equipped with a diode array detector L-2455, a Column Oven L-2300 and a pump L-2130. A RP-18 reversed phase Purospher[®] STAR (Merk) column (250 mm x 4 mm, I.D. 5 μm) was used. Measurements of pH were carried out with a Mettler-Toledo pH-meter. Conductivity was determined using a conductivity meter Mettler Toledo (SevenEasy S30K). All the solutions for HPLC were prepared with ultrapure water obtained with Milli-Q[®] equipment [3].

Results and discussion

Treatment of Tetracycline in aqueous medium was made using electrochemical oxidation, named also electrochemical incineration or cold electrochemical combustion when complete mineralization was achieved. Stainless Steel (SS) and Boron Doped Diamond (BDD) were cathode respectively anode used for this study.

BDD anode has a high oxygen over-potential that permits electrochemical generation in high concentration of radical hydroxyl on the surface of electrode by water oxidation that permits faster mineralization of organics. With a very low activity concerning oxygen formation, oxygen formation potential is 2.3 V/SHE, BDD has a high capacity to produce radical hydroxyl [21, 22].

Radical hydroxyl $\cdot\text{OH}$ is a non-selective, very powerful oxidizing agent able to react with organics giving dehydrogenated or hydroxyleted derivatives until complete mineralization is reached (conversion of organics into CO_2 , water and inorganic ions) [23].

In acidic or neutral medium hydroxyl radical is generated directly at anode surface (Eq. 1).

At $\text{pH} \geq 10$ radical hydroxyl is formed from ion hydroxyl (Eq 3).

$$i_t = nFAD_0 \left(\frac{\partial c_0}{\partial x} \right)_{x=0,t} \quad (4)$$

The combustion efficiency of electrochemical treatment applied to Tetracycline solution was estimated by ratio between TOC and COD decay time [18]. Efficiency of combustion (η_c) calculated is given by Eq 5.

$$\eta_c = \frac{32}{12} \left(\frac{n}{14x} \right) \frac{\Delta\text{TOC}}{\Delta\text{COD}} \quad (5)$$

Degradation reaction of TC in aqueous medium after applying electrochemical treatment will be:

where symbols and units used in above equations, are given in Table1.

Theoretical mathematic model and estimation of COD evolution and of current efficiency in oxidation process in galvanostatic conditions was explained by Comninellis [22]. Variation of limit current intensity in time is expressed as a function of COD.

$$i_{\text{lim}}(t) = nFk_m\text{COD}(t) \quad (7)$$

When $i_{\text{applied}} < i_{\text{lim}}$ concentration of contaminant is too high and electrolysis process is controlled by limit current (randament is 100% and COD linear decrease).

When $i_{\text{applied}} > i_{\text{lim}}$ controlled by phenomena of mass-transport (randament is <100% and COD decrease exponential) and seems like unwished secondary reaction.

In order to find out if the process is controlled by diffusion, average current efficiencies (ACE) [6], were calculated according to the following expression:

$$\text{ACE} = 100 F V \left(\frac{\text{COD}_t - \text{COD}_0}{8 I \Delta t} \right) \quad (8)$$

Average mass transfer coefficients based on COD decay, k_{mCOD} , can be calculated using Eq 9:

$$\text{COD}_t = \text{COD}_0 e^{-\frac{A k_{\text{mCOD}}}{V} t} \quad (9)$$

where symbols used in above equations are explained in Table 1.

Table 1. Symbols and measure units used in equations.

Symbol	Name	Units
$i_{lim}(t)$	limiting current density at given time t	$A \cdot m^{-2}$
$i_{applied}$	applied current density	$A \cdot m^{-2}$
F	Faraday constant (F=96,487)	$C \cdot mol^{-1}$
I	applied current intensity	mA
t	time of electrochemical treatment	s
ΔTOC_{exp}	variation of experimental TOC removal	$mol_C \cdot m^{-3}$
ΔTOC_{theo}	theoretical TOC decay assuming that the applied electrical charge is only consumed in the mineralization process of Tetracycline	$mol_C \cdot m^{-3}$
k_m	coefficient of mass transfer in reactor	$m \cdot s^{-1}$
COD(t)	chemical oxygen demand at time t	$mol_{O_2} \cdot m^{-3}$
COD ₀ (t)	initial chemical oxygen demand	$mol_{O_2} \cdot m^{-3}$
A	electrode geometric area	m^2
V_R	reservoir volume	m^3
V	volume of Tetracycline solution	m^3
i_{lim}^0	Initial limiting current density	$A \cdot m^{-2}$
α	$\alpha = i_{applied} / i_{lim}^0$	
n	number of electrons interchanged	

To study of the influence of experimental conditions on the degradation of the antibiotic, assays were performed at experimental conditions that allow kinetic and/or diffusive control, in order to determine medium mass transfer coefficients to predict degradation rates at experimental conditions other than those tested.

The anodic oxidation of tetracycline was performed in an up-flow reactor, operating in batch mode with recirculation, using as anode a boron-doped diamond electrode.

The evolution of the electrochemical degradation assays with time was followed by: cyclic voltammetry, applied for the study of electrochemically generated free radicals. Cyclic voltammograms are obtained by measuring the current at the working electrode during the potential scan of an electrode immersed in an unstirred solution.

The cyclic voltammograms was obtained for sodium sulphate aqueous solutions, 5 g L⁻¹, without and with tetracycline, 200 mg L⁻¹, at a scan rate of 10 mV s⁻¹. In the voltammogram of the solution that only contains electrolyte, the presence of an oxidation peaks can be detected, before the oxygen evolution, when tetracycline is also present [3]. As it was explained in detail in a previous study [3], the anodic peak detected is due to the contribution of tetracycline oxidation, showing that tetracycline can also be oxidized before oxygen evolution. In the present case, where the target is the complete mineralization of tetracycline, it was used applied current densities high enough to guarantee the formation of hydroxyl radicals.

At different [TC]₀ tetracycline initial concentration (100 and 150 mg L⁻¹) were performed four different assays corresponding to different recirculation flow rate: FR1 = 37 L h⁻¹; FR2 = 75 L h⁻¹; FR3 = 100 L h⁻¹ at constant current density, 300 A m⁻², using as electrolyte a sodium sulfate aqueous solution, 5 g L⁻¹. The duration of the experiments with tetracycline initial concentration of 100 mg L⁻¹ was 4 h. When initial concentration was 150 mg L⁻¹ the duration of the tests was

extended to 6 h, to ensure that almost complete degradation of organic matter was achieved. A summary of the main results obtained in the electrodegradation assays at flow rate 100 L h^{-1} , is presented in Table 2. All these results refer to 4 h assay, in order to make comparison easier.

Table 2. Results obtained after 4h of electrodegradation of TC with different initial tetracycline concentrations on BDD at a recirculation flow rate $\text{FR3} = 100 \text{ L h}^{-1}$

$[\text{TC}]_0^* / \text{mg L}^{-1}$	COD	TOC	ACE / %	$k_{\text{mCOD}} / 10^{-5} \text{ m s}^{-1}$	N-NH ₃ / mg L^{-1} (FINAL)	TKN	TN	Abs _(4 h) Removal / % (360 nm)
100	86	83	1.6	0	3.7	5.2	5.28	99.8
150	93	87	2.5	0	5.1	5.6	5.70	100

For initial concentrations 100 and 150 mg L^{-1} , COD and TOC relative decays increase with flow rate and, for similar recirculation flow rate the removal rate of the organic load increases with initial concentration. These results corresponding to all three recirculation rate ($\text{FR1} = 37 \text{ L h}^{-1}$; $\text{FR2} = 75 \text{ L h}^{-1}$; $\text{FR3} = 100 \text{ L h}^{-1}$) detailed explained in a previous paper [3] where the influence on the degradation rate of tetracycline initial concentration and recirculation flow rate were investigated, assuming that electrodegradation process is under diffusion control. In order to find out if the process is controlled by diffusion, average current efficiencies (ACE) from Table 2, were calculated according to the Eq. 8, obtaining very low values which comes in support of diffusion control.

The elimination of organic matter follows a pseudo-first order kinetic, which can be observed by exponential decay of the relative removal of COD and TOC with time. At the highest degradation rate tested, 100 L h^{-1} , with an initial tetracycline concentration of 150 mg L^{-1} , after 4 h assay, the removals of COD, TOC and absorbance (measured at 276.5 and 360.0 nm) were 93, 87, 99 and 100%, respectively.

The variation of tetracycline concentration with time at different current density values (50, 200, 400, 600 mAcm^{-2}) applied for electrochemical degradation of 100 mg L^{-1} TC, are depicted in Fig 2. The concentration of tetracycline decreases in time. In HPLC analyses the results obtained for this assay (data not shown) indicate that at high current density, the main compound and the metabolites that may occur, are fast degraded at BDD surface. The variation of tetracycline concentration with time in case of degradation of TC solutions with different initial pH, was depicted in Fig 3. The behavior of this TC solutions with different pH are the subject of a future new publication.

Fig. 2. Variation of COD for TC electrochemical degradation ($[\text{TC}]_0 = 100 \text{ mg L}^{-1}$) at different current intensity

Fig. 3. Variation of COD in time for tetracycline degradation at pH (9.81)

It was possible to determinate the mass transfer coefficients, k_m , for the different flow rates (Eq. 13), by calculating Re , Sc and Sh (Eq.10 to 13).

$$Re = \frac{\rho v L}{\mu} \quad (10)$$

$$Sc = \frac{\mu}{\rho D} \quad (11)$$

$$Sh = 0.646 Sc^{1/3} Re^{1/2} \quad (12)$$

$$k_m = \frac{Sh D}{L} \quad (13)$$

where ρ , μ and v are, respectively, density and viscosity of the solution and the linear rate of the solution inside the electrochemical cell. L is the characteristic dimension of the cell, here represented by the hydraulic diameter, defined as the free area for flow over the wet perimeter. The k_m values thus obtained are: FR1 – $5.07 \times 10^{-6} \text{ m s}^{-1}$; FR2 – $7.21 \times 10^{-6} \text{ m s}^{-1}$; FR3 – $8.33 \times 10^{-6} \text{ m s}^{-1}$. Using these k_m and D values, the apparent width of the diffusion layer for the different FRs can be calculated and are 117, 82 and 71 μm , respectively, for FR1, FR2 and FR3.

It was observed that values for $k_{m\text{COD}}$ are higher than for k_m , particularly for the assays run at higher tetracycline initial concentration. As a conclusion the diffusion layer is larger for low flow rate and low initial concentration in tetracycline, and the organics are not oxidized by hydroxyl radicals because they exist mainly near the electrode surface and organic molecules are spread in a larger area. At higher TC initial concentration and low flow rate, the concentration in organics is higher and oxidation by hydroxyl radicals can be more efficient. When flow rate increases, the width of the diffusion layer decreases and the attack by hydroxyl radicals to the organic molecules becomes much easier, leading to increases of rates of oxidation higher than those of mass transfer [3].

CONCLUSIONS

The removal to below the limit of detection of pharmaceuticals (TC) from ground and surface waters destined for drinking water production is obviously imperative. Since conventional drinking water treatments have failed to remove these compounds, it is imperative to develop new technologies suitable for water production plants. Electrodegradation with BDD electrode are promising technologies for electrochemical degradation of TC the high removals of COD show that the metabolites formed during the process are also oxidized, with a high degree of mineralization, since TOC removals are also very high. Average mass transfer coefficients increase with

recirculation flow rate, probably due to a decrease in the width of the diffusion layer that favours the mass transfer process. During the electrodegradation assay the organic nitrogen is mainly converted to ammonium, nitrate and nitrite.

Due to its upstanding properties BDD electrode has multiple applications with a high mineralization degree of TC. In all experimental systems with different electrochemical cells when an up-flow reactor, operating in batch mode with recirculation was used-for degradation of TC solution, is achieved a high degree of removal of pollutants through their complete mineralization of up to 100%. Thus BDD electrode is a great electrode material for multiple applications with excellent results especially in destruction of organics for wastewater treatment from industrial effluents, organic matter oxidation, COD removal, inorganic matter oxidation.

Acknowledgments

This paper was supported by the project "Development and support of multidisciplinary postdoctoral programmes in major technical areas of national strategy of Research - Development - Innovation" 4D-POSTDOC, contract no. POSDRU/89/1.5/S/52603, project co-funded by the European Social Fund through Sectoral Operational Programme Human Resources Development 2007-2013. The authors also want to thank Fundação para a Ciência e a Tecnologia, Portugal.

References

- [1] K. Kümmerer, Antibiotics in the aquatic environment—A review—Part I, *Chemosphere* 75 (2009) 417-434.
- [2] S.A. Sassman, L.S. Lee, Sorption of three tetracyclines by several soils: Assessing the role of pH and cation exchange, *Environmental Science and Technology* 39 (2005) 7452–7459.
- [3] C. I. Brinzila, M.J. Pacheco, L. Ciriaco, R.C. Ciobanu, A. Lopes, Electrodegradation of tetracycline on BDD anode, *Chemical Engineering Journal* 209 (2012) 54-61.
- [4] G. Gu, K.G. Karthikeyan, Interaction of tetracycline with aluminium and iron hydrous oxides, *Environmental Science and Technology* 39 (2005) 2660–2667.
- [5] H. Yamamoto, Y. Nakamura, S. Moriguchi, Y. Nakamura, Y. Honda, I Tamura, Y. Hirata, A. Hayashi, J. Sekizawa, Persistence and partitioning of eight selected pharmaceuticals in the aquatic environment: Laboratory photolysis, biodegradation, and sorption experiments, *Water Research* 43 (2009) 351-362.
- [6] S. Kim, P. Eichhorn, J.N. Jensen, A.S. Weber, D.S. Aga, Removal of antibiotics in wastewater: effect of hydraulic and solid retention times on the fate of Tetracycline in the activated sludge process, *Environmental Science and Technology* 39 (2005) 5816-5823.
- [7] A. Boxall, D. Kolpin, B. Holling-Sorensen, J. Tolls, Are veterinary medicines causing environmental risks? *Environ. Sci. Technol.* 37 (2003) 287A-294A.
- [8] R. Hirsch, T. Ternes, K. Haberer, K.L. Kratz, Occurrence of antibiotics in the aquatic environment, *Sci. Total Environ.* 225 (1999) 109-118.
- [9] S. Kim, P. Eichhorn, J.N. Jensen, A.S. Tweber, D.S. Aga, Removal of antibiotics in wastewater: Effect of hydraulic and solid retention times on the fate of tetracycline in the activated sludge process, *Environ. Sci. Technol.* 39 (2005) 5816-5823.
- [10] Y. Liu, X. Gan, B. Zhou, B. Xiong, J. Li, C. Dong, J. Bai, W. Cai, Photoelectrocatalytic degradation of tetracycline by highly effective TiO₂ nanopore arrays electrode, *J. Hazard. Mater.* 171 (2009) 678–683.
- [11] R.A. Palominos, M.A. Mondaca, A. Giraldo, G. Peñuela, M. Pérez-Moya, H.D. Mansilla, Photocatalytic oxidation of the antibiotic tetracycline on TiO₂ and ZnO suspensions, *Catal. Today* 144 (2009) 100–105.
- [12] P. Wang, P-S. Yap, T.T. Lim, C–N–S tridoped TiO₂ for photocatalytic degradation of tetracycline under visible-light irradiation, *Appl. Catal. A: Gen.* 399 (2011) 252–261.

- [13] J. Jeong, W. Song, W.J. Cooper, J. Jung, J. Greaves, Degradation of tetracycline antibiotics: Mechanisms and kinetic studies for advanced oxidation/reduction processes, *Chemosphere* 78 (2010) 533–540.
- [14] M.D. Vendenyapina, Y.N. Eremicheva, V.A. Pavlov, A.A. Vendenyapin, Electrochemical degradation of tetracycline, *Russ. J. Appl. Chem.* 8 (2008) 800-802.
- [15] A. Rossi, V.A. Alves, L.A. Da Silva, M.A. Oliveira, D.O.S. Assis, F.A. Santos, R.R.S. De Miranda, Electrooxidation and inhibition of the antibacterial activity of oxytetracycline hydrochloride using RuO₂ electrode, *J. Appl. Electrochem.* 39 (2009) 329-337.
- [16] H. Zhang, F. Liu, X.G. Wu, J.H. Zhang, D.B. Zhang, Degradation of tetracycline in aqueous medium by electrochemical method, *Asia-Pac. J. Chem. Eng.* 4 (2009) 568–573.
- [17] M. Miyata, I. Ihara, G. Yoshid, K. Toyod K. Umetsu, Electrochemical oxidation of tetracycline antibiotics using a Ti/IrO₂ anode for wastewater treatment of animal husbandry, *Wat. Sci. Technol.* 63 (2011) 456-461.
- [18] L. Ciriaco, C. Anjo, J. Correia, M.J. Pacheco, A. Lopes, Electrochemical degradation of Ibuprofen on Ti/Pt/PbO₂ and Si/BDD electrodes, *Electrochim. Acta*, 54 (2009) 1464–1472.
- [19] M. Panizza, G. Cerisola, Application of diamond electrodes to electrochemical processes, *Electrochim. Acta* 51 (2005) 191.
- [20] I. Sirés, E. Brillas, Remediation of water pollution caused by pharmaceutical residues based on electrochemical separation and degradation technologies: A review, *Environment International* 40 (2012) 212-229.
- [21] Ch. Comninellis, C. Pulgarin, Anodic oxidation of phenol for wastewater treatment, *J. Appl. Electrochem.* 21 (1991) 703-708.
- [22] Ch. Comninellis, C. Pulharin, Electrochemical oxidation of phenol for wastewater treatment using SnO₂ anodes, *J. Appl. Electrochem.* 23 (1993) 108-112.
- [23] Ch. Comninellis, Application of synthetic BDD electrodes in electrooxidation, in *Diamond Electrochemistry*, Elsevier, Amsterdam (2005) 449-476.