

Foreword: Advances in Crack Growth Modelling

Ferri Aliabadi^{1, a}, Pihua Wen^{2, b}

¹Imperial College London, South Kensington, London SW7 2BY

²Queen Mary, University of London, Mile End Road, London, TS1 4EN

^am.h.aliabadi@imperial.ac.uk, ^bP.H.Wen@qmul.ac.uk

Fatigue failure of structures is normally caused by cracks that extend beyond a safe size. Flaws are present to some extent in all structural parts, either as a result of manufacturing fabrication defects or damage in service. Crack growth is a complex phenomenon to model and simplifications are assumed. In recent years, there has been an increasing realisation that advanced computational methods such as the Finite Element Method, the Boundary Element Method and Meshfree Methods can be used to simulate crack growth in complex structural parts.

Early works to model crack growth using the Finite Element Method (FEM) can be traced back to works of Shephard et al [1] and, Valliappan and Marti[2]. More recent advances in the finite element method can be found in the work of Theilig et al [3] for two-dimensional mixed-mode crack problems, Buchholz and Richard [4], Citarella and Buchholz [5] and Li et al [6] for three – dimensional mixed-mode problems.

A recent successful application of the FEM to mixed-model crack growth modelling is due to the development of eXtended Finite Element Method (XFEM). The XFEM as developed by Black and Belytscho[7] and Rethore et al [8] are inspired by the enriched finite elements originally proposed by Benzely [9] and Foschi and Barrett[10] (see Aliabadi and Rooke[11] for an overview of enriched FEM). The work by Belytschko and Black enabled the enrichment of finite element approximations requiring minimal remeshing to solve crack growth problems. The partition of unity property of finite elements was later used in XFEM which allowed enriching of regions near the discontinuities. This method offers some unique advantages over earlier FEM methods proposed to model crack growth in structures. It does not require any projections between the meshes and has proved to be far better than finite element methods with continuous remeshing. The advantage of XFEM lies in the fact that it subdivides the crack problem into two parts where a mesh is generated without cracks/inclusions and then finite element functions can be enriched to simulate discontinuities. Belytschko and Black treated curved discontinuities by mapping a straight crack enrichment field which was further developed by Dolbow *et al.* [12] and Moes *et al.*[13]. Sukumar *et al.* [14] implemented the concept of Partition of Unity and XFEM to three dimensional problems by using a discontinuous function to simulate the crack surface and enriching the crack front by 2D asymptotic crack tip displacement fields.

The Boundary Element Method (BEM) has also a long history in fracture mechanics and crack growth modelling [11]. A robust method for modeling crack growth in general mixed-mode problems was developed by Portela, et al[12,13] and Mi and Aliabadi [14]. The method was an extension of the Dual Boundary Element Method (DBEM) earlier proposed by the same authors, as an effective way of modeling crack problems using the boundary integral equation. The DBEM was the first computational method that allowed modelling of mixed-mode crack problems without a need for continuous remeshing and user interferences. The crack extension was modelled with new boundary elements without having to remesh the previous crack geometry. Hence, the method remains the only computational method that is truly mesh independent. Early benchmarks used in [14] for the first times such as the mixed mode growth of an inclined elliptical crack have since been repeated in XFEM and Meshfree publications. In addition, DBEM has established itself as one of the most accurate numerical methods for the evaluation of stress intensity factors which is

the key parameter for fatigue life assessment of structures. The extension of the DBEM to different linear, transient and nonlinear problems can be found in [15-25].

During the last decades, mesh-free methods, as an alternative to FEM and BEM have shown a promising potential and has found applications in fracture mechanics. Among different types of mesh-free methods proposed so far, Element free Galerkin and Meshless local Petrov-Galerkin (MLPG) have gained much attention both using Moving least square (MLS) approximation as the shape function construction. More recent, applications are reported in [27-31].

This special issue of *Key Engineering Materials* contains original papers written by active researchers in the field of computational fracture mechanics. The aim is to inform those in the fracture mechanics community who might not be at the forefront of computational research of the recent developments and techniques available and the wide range of applications for which solutions are now possible.

Editors
April 2013

References

- [1] Shepard, M.S., et al (1985): Automatic crack propagation tracking, *Computers and Structures*, vol 20, 211-223.
- [2] Valliappan, S and Murti, V (1985) Automatic remeshing technique in quasi-static and dynamic crack propagation. *Proce. NUMETA, 85 Conf.*, pp 107-116
cracks in pure bending, *Engineering Fracture Mechanics*, vol. 37, no. 2, pp. 323-40.
- [3] Theilig, H., et al (1997): higher order fatigue crack path simulation by the MVCCI-method. In B.L.Karihaloo et al (eds), *Advances in Fracture Research*, vol 4, Pergamon Press, Amsterdam, 2235-2242.
- [4] Buchholz, F.-G; et al (2004): Fracture analyses and experimental results of crack growth under general mixed mode loading conditions. *Engineering Fracture Mechanics*, vol. 71, 455-468.
- [5] Citarella, R and Buchholz F-G (2007) Comparison of DBEM and FEM crack path predictions with experimental findings for a SEN-specimen under anti-plane shear loading, *Key Engineering Materials*, vols 348-349, 29-132.
- [6] Li Qing-fen, et al (2010) Computational analysis of the AFM specimen on mixed-mode II and III fracture, *Key Engineering Materials*, vols 452-453, 73-176.
- [7] Black, T and Belytschko, T (1999) Elastic crack growth in finite elements with minimal remeshing, *International Journal for Numerical Methods in Engineering*, vol. 45, 601-620
- [8] Rethore, J, et al (2005) An energy-conserving scheme for dynamic crack growth using the eXtended finite element method, *International Journal for Numerical Methods in Engineering*, vol. 63, 631-659.
- [9] Benzley, S.E. (1974): Representation of singularities with isoparametric finite elements, *International Journal for Numerical Methods in Engineering*, vol. 8, 1333-1336
- [10] Foschi, R.O. and Barrett, J.D. (1976) Stress intensity factors in anisotropic plates using singular elements, *International Journal for Numerical Methods in Engineering*, vol. 10, 1281-1287.
- [11] Aliabadi, M.H. and Rooke, D.P. (1991): *Numerical Fracture Mechanics*, Computational Mechanics Publications, Southampton, UK and Kluwer Academic Publishers, Dordrecht, Netherlands
- [12] Portela, A., Aliabadi, M.H., Rooke, D.P., (1993) Dual boundary incremental analysis of crack propagation, *Computer and Structures*, vol. 46, 237-247.

- [13] Portela, A., et al (1992) Dual boundary element analysis of cracked plates – singularity subtraction technique, *International Journal of Fracture*, vol. 55, 17-28
- [14] Mi Y. and Aliabadi M.H. (1992): Dual boundary element method for three-dimensional fracture mechanics analysis. *Engineering Analysis with Boundary Elements*, vol. 10, 161-171.
- [15] Fedelinski,P, et al (1996) The Laplace transform DBEM for mixed-mode dynamic crack analysis, *Computers and Structures*, 59, 1021-1031.
- [16] Cisilino, A.P. and Aliabadi, M.H. (1997): Three-dimensional BEM analysis for fatigue crack growth in welded components. *International Journal of Pressure Vessels and Piping*, vol. 70, 135-144.
- [17] Dirgantara, T and Aliabadi, M H (2000) Crack growth analysis of plates loaded by bending and tension using dual boundary element method *International Journal of Fracture*, vol. 105, 27-47
- [18] Fedelinski, P, et al (1997) The time-domain DBEM for rapidly growing cracks *International Journal for Numerical Methods in Engineering*, vol. 40, 1555-1572
- [19] Albuquerque, EL; et al (2004) Dual boundary element method for anisotropic dynamic fracture mechanics, *International Journal for Numerical Methods in Engineering*, vol. 59, 1187-1205
- [20] Saleh, A L and Aliabadi M H (1995) Crack growth analysis in concrete using boundary element method *Engineering Fracture Mechanics*, vol. 51,533-545.
- [21] Salgado, N K and Aliabadi, M H (1996) The application of the dual boundary element method to the analysis of cracked stiffened panels *Engineering Fracture Mechanics* vol. 54, 91-105
- [22] Sfantos,G K and Aliabadi, M H (2007) Multi-scale boundary element modelling of material degradation and fracture. *Computer Methods in Applied Mechanics and Engineering*, vol. 196, 1310-1329
- [23] Wen,P H, et al (2004) Crack growth analysis for multi-layered airframe structures by boundary element method *Engineering Fracture Mechanics*, vol. 71, 619-631
- [24] Fedelinski, P; Aliabadi, MH; (1996) Boundary element formulations for the dynamic analysis of cracked structures, *Engineering Analysis with Boundary Elements*, vol. 17,45-56
- [25] Di Pisa, C.; et al (2012) Dual boundary method for assembled plate structures undergoing large deflection *International Journal for Numerical Methods in Engineering*, vol. 89, 1720-1738
- [26] Di Pisa, C.; Aliabadi, M. H. (2013) Fatigue crack growth analysis of assembled plate structures with dual boundary element method *Engineering Fracture Mechanics*, vol. 98, 200-213
- [27]Wen,P.H et al (2008) Meshless method for crack analysis in functionally graded materials with enriched radial base functions, *CMES: Computer Modeling in Engineering & Sciences* vol. 30, 133-147
- [28] Wen, P. H.; Aliabadi, M. H (2011) A variational approach for evaluation of stress intensity factors using the element free Galerkin method, *International Journal of Solids and Structures*, vol 48, 1171-1179
- [29] Wen, P. H.; Aliabadi, M. H. (2009) Evaluation of mixed-mode stress intensity factors by the mesh-free Galerkin method: static and dynamic, *Journal of Strain Analysis for Engineering Design*, vol 44,273-286
- [30] Rabczuk, T. et al (2010) On three-dimensional modelling of crack growth using partition of unity methods, *Computers & Structures*, vol 88, 1391-411.
- [31] Barbieri,E, et al (2012) A new weight-function enrichment in meshless methods for multiple cracks in linear elasticity, *International Journal for Numerical Methods in Engineering*, vol. 90, 177-95.