
Table of Contents

Flow Stoppage in the Middle Area of Flow Length Occurs at Thin Die Gap T. Haga, H. Sakaue, H. Fuse and H. Watari	1
Three-Dimensional Geometrically Exact Dynamic Modeling of Electrohydrodynamic Direct-Writing under a Non-Uniform Electric Field G.Z. Wang, W. Chen, J.K. Chen, C. Hu and Z.P. Yin	9
Electrohydrodynamic Printing Droplet Volume Control Using Supervised Learning Z.W. Zhao, W. Chen, Y.J. Zhu and J.K. Chen	17
Experimental Validation of EMIS-Based Frequency Tracking for Milling Vibration Monitoring Compared with FFT Analysis G. Haydarlar, M.A. Sofuoğlu and M. Tekkalmaz	23
FRT-Net: A Lightweight Frequency-Spatial Framework for Low-Light Enhancement via Retinex Decomposition and FFT Filtering D. Guo and Y. Han	33
Performance Analysis of a 20 Gbps Bidirectional TWDM PON for Different Modulation Formats A. Begam and M.A. Sekh	49
Experimental Investigation of Corona Discharge in Wire-Cylinder Electrostatic Precipitators H. Nouri, H.A. Said and K. Meziane	61
Effects of Staircase Core Configuration on the Seismic Behaviour of Reinforced Concrete Frame Structures S. Louadj, A. Louzai, L. Tahraoui and M. Ouanani	73